

Processing instructions

The lacquer for sheet wax can be applied very thin with a brush on the sheets. After drying the lacquer inhibits partial solution of the wax sheets caused by the containing solvents in the release agent, which is applied afterwards. Furthermore it prevents trickling down of the PVA-film on the wax sheets.

In General

Sales units / packages: 1,000 l / 5,000 l

Storing

At room temperature (18 – 25°C) and closed original containers storage life is 6 months.
Partly used containers have to be closed always and the material has to be used up as soon as possible.

Keep away from ignition sources
Do not store outdoors.
In case of extreme cold do stabilize to 15 °C.

Safety measure

Please follow the precautions of the Government Safety Organisation of the chemical industry when working with this material.
Please follow safety advices !

Waste Disposal

According to arrangement with local authorities cured material can be disposed as domestic or commercial waste.

In case of further questions please do not hesitate to contact our Department for Product Safety.

The instructions and recommendations are given in good faith and are based on long experience and careful tests. Since the conditions of use are beyond our control, and due to versatility of applications and working methods, we can't give any guarantee. All information are non-binding and are no guarantee for special characteristics or properties of the product. Despite information given from **ebalta** the customer has to make his own tests regarding applications and processing. If any special warranty is requested, written agreement on this subject is essential.

ebalta UK Limited . B2 Langham Park, Trent Lane . Castle Donington . Derbyshire DE74 2UT
t: +44 1332 814700 . f: +44 1332 814775 . e: info@**ebalta**.co.uk . w: www.**ebalta**.co.uk